

# Material Safety Data Sheet

## 1. Product & Company Identification:

Product	Li-Polymer Battery
Manufacturer:	Conrad Electronic SE
Model:	LiPo Racing Pack 7.4V / 3300mAh / 25C
Nominal capacity:	3300mAh
Nominal voltage:	7.4V
Address:	Klaus-Conrad-Strasse 1, D-92242 Hirschau
Telephone:	+ 49 9604408833
Date of issue:	18.10.2010

## 2. Composition /Information on Ingredients:

MATERIAL OR INGREDIENT	CAS Index No./EC No.	Molecular formula	Percent
Cobalt lithium dioxide	12190-79-3	LiCoO2	20-35%
Aluminium	7429-90-5	Al	10-15%
Lithium	7439-93-2	Li	10-15%
Lithium hexafluorophosphate(1-)	21324-40-3		3-7%
Carbon black	1333-86-4		2-5%
Nickel	7440-02-0	Ni	1-2%
Polyvinylidene fluoride	24937-79-9		3-6%
Graphite	7782-42-5	С	10-16%
Copper	7440-50-8	Cu	15-20%

Remark: cobalt lithium dioxide (CAS No.: 12190-79-3) Synonym: lithium cobalt(III) oxide



## Material Safety Data Sheet

#### 3. Hazardous Identification:

#### Hazard description:

Not applicable.

#### Information pertaining to particular dangers for man and environment:

A sealed polymer battery is not hazardous in normal use on pinciple.

The product has not to be labelled due to the calculation procedure of international guideline.

The materials contained in this product may only represent below hazard if the integrity of the battery is compromised; physically or electrically abused.

Harmful in contact with skin.

Causes burns.

Limited evidence of a carcinogenic effect.

May cause sensitisation by inhalation and skin contact.

Reacts violently with water, liberating extremely flammable gases.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

#### Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

#### NFPA ratings (scale 0 - 4)

Health = 0
Fire = 0
Reactivity = 0

### HMIS-ratings (scale 0 - 4)

Health = 0 HEALTH 0
Fire = 0 FIRE 0
Reactivity = 0

#### 4. First Aid Measures:

**General information:** If exposure to internal materials within battery due to damaged outer casing, the following actions are recommended.

**After inhalation:** Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.



## Material Safety Data Sheet

### 5. Fire Fighting Measures:

Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water

Protective equipment: Wear fully protective suit.

#### 6. Accidental Release Measures:

**Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.

Measures for environmental protection: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

Measures for cleaning/collecting: Use neutralizing agent. Dispose contaminated material as waste according to item 13.

sure adequate ventilation. Do not flush with water or aqueous cleansing agents

Additional information: See Section 7 for information on safe handling.

### 7. Handling & Store:

#### a) Handling:

Information for safe handling: No special measures required.

Information about protection against explosions and fires:

- · Protect from heat.
- · Protect against electrostatic charges.
- Prevent impact and friction.

#### b) Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Store away from flammable substances.

Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles



# Material Safety Data Sheet

## 8. Exposure Control/Personal Protection:

Additional information about design of technical systems: No further data; see item 7.

7429-90-5 aluminium	Components with limit values that require monitoring at the workplace:		
Metal dust "total dust "respirable fraction   10" 5" mg/m³	· · · · · · · · · · · · · · · · · · ·		
REL (USA)	PEL (USA)	15* 5** mg/m³	
Metal dust "total dust "respirable fraction 1" mg/m³ are respirable fraction 10" 4** mg/m³ are respirable fraction 10" 4** mg/m³ arinhalable dust "respirable dust" "respirable dust "respirabl	, ,		
TLV (USA)	REL (USA)		
WEL (Great Britain)         "as respirable fraction 10" 4" mg/m³ minhalable dust "respirable dust           7782-42-5 Graphite           PEL (USA)         15 mppcf mg/m³ (2.5" mg/m³ (respirable dust)           TLV (USA)         2" mg/m³ (all forms except graphite fibers; "resp. fraction)           7440-50-8 copper           PEL (USA)         1" 0.1" mg/m³ (as Cu "dusts and mists "fume)           REL (USA)         1" 0.1 R" mg/m³ (as Cu "dusts and mists "fume)           TLV (USA)         5hort-term value: 0.1" mg/m³ (austs and mists; "fume; as Cu           WEL (Great Britain)         5hort-term value: 2" mg/m³ (austs and mists; "fume; as Cu           WEL (Great Britain)         3.5 mg/m³ (austs and mists; "fume; as Cu           TAUSAS (as Cu)           1333-86-4 Carbon black           PEL (USA)         3.5 mg/m³ (austs and mists) (as Cu)           1333-86-4 Carbon black           PEL (USA)         3.5 mg/m³ (austs) (as Cu)           1440-02-0 nickel           PEL (USA)         1 mg/m³ (austs) (as Cu)           7440-02-0 nickel           PEL (USA)         1 mg/m³ (austs) (as Cu)           1 mg/m³ (austs) (as Cu)           1 mg/m³ (austs) (as Cu)			
WEL (Great Britain)         10" 4"" mg/m³ "inhalable dust "respirable dust           7782-42-5 Graphite           PEL (USA)         15 mppcf mg/m³ (respirable dust)           TLV (USA)         2.5" mg/m³ (respirable dust)           TLV (USA)         2" mg/m³ (all forms except graphite fibers; resp. fraction)           7440-50-8 copper           PEL (USA)         1" 0.1" mg/m³ (as Cu "dusts and mists "fume)           REL (USA)         1" 0.1 R"* mg/m³ (as Cu "dusts and mists "fume)           TLV (USA)         Short-term value: 0.1" mg/m³ (aust and mists "fume)           WEL (Great Britain)         Short-term value: 1" 0.2" mg/m³ (aust and mists)           WEL (Great Britain)         Short-term value: 2" mg/m³ (aust and mists)           1333-86-4 Carbon black           PEL (USA)         3.5 mg/m³ (aust and mists)           12 mg/m³ (aust and mists)           1333-86-4 Carbon black           PEL (USA)         3.5 mg/m³ (aust and mists)           14 mg/m³ (aust and mists)           14 mg/m³ (aust and mists)           15 mg/m³ (a	TLV (USA)	1* mg/m <sup>3</sup>	
"inhalable dust "*respirable dust           7782-42-5 Graphite           PEL (USA)         15 mppcf mg/m³           REL (USA)         2.5" mg/m³           "respirable dust         1*UV (USA)           2" mg/m³         all forms except graphite fibers; "resp. fraction           7440-50-8 copper           PEL (USA)         1" 0.1" mg/m³           as Cu "dusts and mists "fume           REL (USA)         1" 0.1" mg/m³           as Cu "dusts and mists "fume           Cu Usts and mists "fume           Short-term value: 0.1" mg/m³           Long-term value: 1" 0.2" mg/m³           dusts and mists; "fume           Short-term value: 1" 0.2" mg/m³           Long-term value: 2" mg/m³           Long-term value: 0.2" 1" mg/m³           REL (USA)         3.5 mg/m³           VALO-2.0 nickel           PEL (USA)         1 mg/m³			
7782-42-5 Graphite           PEL (USA)         15 mppcf mg/m³           REL (USA)         2.5" mg/m³           "respirable dust         2" mg/m³           all forms except graphite fibers; "resp. fraction           7440-50-8 copper           PEL (USA)           1* 0.1* " mg/m³           as Cu "dusts and mists "fume           REL (USA)         1* 0.1 R* mg/m³           as Cu "dusts and mists "fume           Short-term value: 0.1* mg/m³           Long-term value: 1* 0.2** mg/m³           Long-term value: 2** mg/m³           Long-term value: 0.2* mg/m³           VEL (USA)         3.5 mg/m³           VEL (Great Britain)         Short-term value: 7 mg/m³           VEL (Great Britain)         Short-term value: 3.5 mg/m³           7440-02-0 nickel           PEL (USA)         1 mg/m³           REL (USA)         0.015 mg/m³           Elemental: as inhalable fraction         0	WEL (Great Britain)		
PEL (USA)         15 mppcf mg/m³           REL (USA)         2.5° mg/m³           "respirable dust           TLV (USA)         2° mg/m³           all forms except graphite fibers; "resp. fraction           7440-50-8 copper           PEL (USA)         1° 0.1° mg/m³           as Cu "dusts and mists **fume           REL (USA)         1° 0.1 R° mg/m³           as Cu "dusts and mists **fume           TLV (USA)         Short-term value: 0.1° mg/m³           Long-term value: 1° 0.2° mg/m³           "dusts and mists; **fume; as Cu           WEL (Great Britain)         Short-term value: 2° mg/m³           Long-term value: 0.2° 1° mg/m³           *0.1 in presence of PAHs, as PAHs; 10-hr TWA           3.5 mg/m³           WEL (Great Britain)         Short-term value: 7 mg/m³           Long-term value: 3.5 mg/m³           VEL (Great Britain)         1 mg/m³           Long-term value: 3.5 mg/m³           Elemental         1.5° mg/m³           Elemental         1.5° mg/m³           Elemental         1.5° mg/m³		*inhalable dust **respirable dust	
REL (USA)         2.5" mg/m³	7782-42-5 Graphite		
TLV (USA)         2" mg/m³ all forms except graphite fibers; "resp. fraction           7440-50-8 copper           PEL (USA)         1" 0.1*" mg/m³ as Cu "dusts and mists *"fume           REL (USA)         1" 0.1 R*" mg/m³ as Cu "dusts and mists *"fume           TLV (USA)         Short-term value: 0.1*" mg/m³ Long-term value: 1" 0.2*" mg/m³ dusts and mists; "fume: as Cu           WEL (Great Britain)         Short-term value: 2*" mg/m³ Long-term value: 2*" mg/m³ Long-term value: 0.2* 1*" mg/m³ *fume *"dusts and mists (as Cu)           1333-86-4 Carbon black           PEL (USA)         3.5 mg/m³ 70.1 in presence of PAHs, as PAHs; 10-hr TWA           TLV (USA)         3.5 mg/m³ Short-term value: 7 mg/m³ Long-term value: 3.5 mg/m³ Long-term value: 0.1**			
TLV (USA)         2* mg/m³ all forms except graphite fibers;*resp. fraction           7440-50-8 copper           PEL (USA)         1* 0.1** mg/m³ as Cu *dusts and mists **fume           REL (USA)         1* 0.1 R** mg/m³ as Cu *dusts and mists **fume           TLV (USA)         Short-term value: 0.1** mg/m³ as Cu *dusts and mists **fume           VEL (Great Britain)         Short-term value: 1* 0.2** mg/m³ and mists and mists (as Cu)           **Jung-term value: 0.2** mg/m³ and mists (as Cu)           *Jung-term value: 0.2** mg/m³ and mists (as Cu)           <	REL (USA)		
all forms except graphite fibers;*resp. fraction  7440-50-8 copper  PEL (USA)  1* 0.1** mg/m³ as Cu *dusts and mists **fume  1* 0.1 R** mg/m³ as Cu *dusts and mists **fume  TLV (USA)  1* 0.1 R** mg/m³ as Cu *dusts and mists **fume  TLV (USA)  Short-term value: 0.1** mg/m³ Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu  WEL (Great Britain)  Short-term value: 0.2* 1** mg/m³ Long-term value: 0.2* 1** mg/m³ *dusts and mists (as Cu)  1333-86-4 Carbon black  PEL (USA)  REL (USA)  3.5 mg/m³ *0.1 in presence of PAHs, as PAHs; 10-hr TWA  1LV (USA)  WEL (Great Britain)  Short-term value: 7 mg/m³ Long-term value: 3.5 mg/m³ 7440-02-0 nickel  PEL (USA)  REL (USA)  1 mg/m³ Elemental TLV (USA)  1.5* mg/m³ Elemental; *as inhalable fraction  WEL (Great Britain)  0.5 mg/m³  Elemental; *as inhalable fraction  WEL (Great Britain)  0.5 mg/m³			
T440-50-8 copper	TLV (USA)		
PEL (USA)         1* 0.1** mg/m³ as Cu *dusts and mists **fume           REL (USA)         1* 0.1 R** mg/m³ as Cu *dusts and mists **fume           TLV (USA)         Short-term value: 0.1** mg/m³ Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu           WEL (Great Britain)         Short-term value: 2** mg/m³ Long-term value: 0.2* 1** mg/m³ *fume ***dusts and mists (as Cu)           1333-86-4 Carbon black           PEL (USA)         3.5 mg/m³ 3.5* mg/m³ *0.1 in presence of PAHs, as PAHs; 10-hr TWA           TLV (USA)         3.5 mg/m³ Short-term value: 7 mg/m³ Long-term value: 3.5 mg/m³ *0.01 in presence of PAHs, as PAHs; 10-hr TWA           7440-02-0 nickel         TEL (USA)           PEL (USA)         1 mg/m³ Long-term value: 3.5 mg/m³ *0.015 mg/m³ Elemental           TLV (USA)         1.5* mg/m³ Elemental           TLV (USA)         1.5* mg/m³ Elemental; as inhalable fraction           WEL (Great Britain)         0.5 mg/m³		all forms except graphite fibers;*resp. fraction	
As Cu *dusts and mists **fume			
REL (USA)       1* 0.1 R** mg/m³ as Cu *dusts and mists **fume         TLV (USA)       Short-term value: 0.1** mg/m³ Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu         WEL (Great Britain)       Short-term value: 2** mg/m³ Long-term value: 0.2* 1** mg/m³ *fume **dusts and mists (as Cu)         1333-86-4 Carbon black         PEL (USA)       3.5 mg/m³ 3	PEL (USA)		
as Cu *dusts and mists **fume Short-term value: 0.1** mg/m³ Long-term value: 1* 0.2** mg/m³ *dusts and mists; **fume; as Cu  WEL (Great Britain)  WEL (Great Britain)  **Tumper value: 0.2** mg/m³ *dusts and mists (as Cu)  **Tumper value: 0.2** 1** mg/m³ *fume **dusts and mists (as Cu)  **Tumper value: 0.2** 1** mg/m³ *fume **dusts and mists (as Cu)  **Tumper value: 0.2** 1** mg/m³ *fume **dusts and mists (as Cu)  **Tumper value: 0.2** 1** mg/m³ *fume **dusts and mists (as Cu)  **Tumper value: 0.2** 1** mg/m³ *fume **Tumper value: 0.2** 1** mg/m³ *fume **Tumper value: 7 mg/m³ *fume **Tumper value: 7 mg/m³ *fume **Tumper value: 3.5 mg/m³	55. (1.0.1)		
TLV (USA)       Short-term value: 0.1** mg/m³         Long-term value: 1* 0.2** mg/m³         *dusts and mists; **fume; as Cu         WEL (Great Britain)       Short-term value: 2** mg/m³         Long-term value: 0.2* 1** mg/m³ *fume         **dusts and mists (as Cu)         1333-86-4 Carbon black         PEL (USA)         REL (USA)       3.5 mg/m³         *0.1 in presence of PAHs, as PAHs; 10-hr TWA         TLV (USA)       3.5 mg/m³         WEL (Great Britain)       Short-term value: 7 mg/m³         Long-term value: 3.5 mg/m³         7440-02-0 nickel         PEL (USA)         REL (USA)       0.015 mg/m³         Elemental       1.5* mg/m³         Elemental; *as inhalable fraction         WEL (Great Britain)       0.5 mg/m³	REL (USA)		
Long-term value: 1* 0.2** mg/m³     *dusts and mists; **fume; as Cu  Short-term value: 2** mg/m³     Long-term value: 0.2* 1** mg/m³ *fume     **dusts and mists (as Cu)  1333-86-4 Carbon black  PEL (USA)     REL (USA)     3.5 mg/m³     *0.1 in presence of PAHs, as PAHs; 10-hr TWA  TLV (USA)     3.5 mg/m³     WEL (Great Britain)     Short-term value: 7 mg/m³     Long-term value: 3.5 mg/m³  PEL (USA)  7440-02-0 nickel  PEL (USA)     1 mg/m³     REL (USA)     1.5* mg/m³     Elemental  TLV (USA)     1.5* mg/m³     Elemental;*as inhalable fraction  WEL (Great Britain)  WEL (Great Britain)  WEL (Great Britain)  O.5 mg/m³	TIV/(IICA)		
*dusts and mists; **fume; as Cu Short-term value: 2** mg/m³ Long-term value: 0.2* 1** mg/m³ *fume **dusts and mists (as Cu)  1333-86-4 Carbon black  PEL (USA) REL (USA) REL (USA) 3.5 mg/m³ *0.1 in presence of PAHs, as PAHs; 10-hr TWA  TLV (USA) WEL (Great Britain) Short-term value: 7 mg/m³ Long-term value: 3.5 mg/m³  7440-02-0 nickel  PEL (USA) REL (USA)	TLV (USA)		
WEL (Great Britain)  Short-term value: 2** mg/m³ Long-term value: 0.2* 1** mg/m³ *fume  **dusts and mists (as Cu)  1333-86-4 Carbon black  PEL (USA)  REL (USA)  3.5 mg/m³  *0.1 in presence of PAHs, as PAHs; 10-hr TWA  TLV (USA)  WEL (Great Britain)  Nort-term value: 7 mg/m³ Long-term value: 3.5 mg/m³  7440-02-0 nickel  PEL (USA)  REL (USA)  REL (USA)  PEL (USA)  REL (USA)  O.015 mg/m³ Elemental  TLV (USA)  USA  REL (USA)  O.5 mg/m³ Elemental:*as inhalable fraction  WEL (Great Britain)  VEL (Great Britain)			
Long-term value: 0.2* 1** mg/m³ *fume  **dusts and mists (as Cu)  1333-86-4 Carbon black  PEL (USA)  REL (USA)  3.5 mg/m³  *0.1 in presence of PAHs, as PAHs; 10-hr TWA  TLV (USA)  WEL (Great Britain)  Short-term value: 7 mg/m³ Long-term value: 3.5 mg/m³  7440-02-0 nickel  PEL (USA)  REL (USA)  REL (USA)  1 mg/m³ Elemental  TLV (USA)  1.5* mg/m³ Elemental;*as inhalable fraction  WEL (Great Britain)  0.5 mg/m³	WEL (Croot Pritoin)		
**dusts and mists (as Cu)         1333-86-4 Carbon black         PEL (USA)       3.5 mg/m³         REL (USA)       3.5 mg/m³         *0.1 in presence of PAHs, as PAHs; 10-hr TWA         TLV (USA)       3.5 mg/m³         WEL (Great Britain)       Short-term value: 7 mg/m³         Long-term value: 3.5 mg/m³         7440-02-0 nickel         PEL (USA)       1 mg/m³         REL (USA)       0.015 mg/m³         Elemental         TLV (USA)       1.5* mg/m³         Elemental;*as inhalable fraction         WEL (Great Britain)       0.5 mg/m³	WEL (Great Britain)		
1333-86-4 Carbon black         PEL (USA)       3.5 mg/m³         REL (USA)       3.5 mg/m³         *0.1 in presence of PAHs, as PAHs; 10-hr TWA         3.5 mg/m³         WEL (Great Britain)       Short-term value: 7 mg/m³         Long-term value: 3.5 mg/m³         7440-02-0 nickel         PEL (USA)         REL (USA)       0.015 mg/m³         Elemental         TLV (USA)       1.5* mg/m³         Elemental;*as inhalable fraction         WEL (Great Britain)       0.5 mg/m³			
PEL (USA)  REL (USA)  3.5 mg/m³  *0.1 in presence of PAHs, as PAHs; 10-hr TWA  3.5 mg/m³  Short-term value: 7 mg/m³  Long-term value: 3.5 mg/m³  7440-02-0 nickel  PEL (USA)  REL (USA)  REL (USA)  TLV (USA)  1 mg/m³  0.015 mg/m³  Elemental  TLV (USA)  1.5* mg/m³  Elemental;*as inhalable fraction  0.5 mg/m³	1333-86-4 Carbon black	, ,	
REL (USA)  3.5* mg/m³ *0.1 in presence of PAHs, as PAHs; 10-hr TWA  3.5 mg/m³ WEL (Great Britain)  Short-term value: 7 mg/m³ Long-term value: 3.5 mg/m³  7440-02-0 nickel  PEL (USA)  REL (USA)  REL (USA)  1 mg/m³ Clemental  TLV (USA)  1.5* mg/m³ Elemental;*as inhalable fraction  WEL (Great Britain)  3.5* mg/m³ Cong-term value: 7 mg/m³ Cong-term value: 3.5 mg/m³ Elemental  TLV (USA)  0.015 mg/m³ Elemental;*as inhalable fraction  0.5 mg/m³			
*0.1 in presence of PAHs, as PAHs; 10-hr TWA 3.5 mg/m³  WEL (Great Britain)  **7440-02-0 nickel**  PEL (USA)  REL (USA)  TLV (USA)  **1 mg/m³  **2 clemental  **1 mg/m³  **2 clemental  **3.5 mg/m³  **3 clemental  **1 mg/m³  **3 clemental  **4 clemental  **4 clemental  **5 mg/m³  **5 mg/m²  **5 mg/			
TLV (USA)       3.5 mg/m³         WEL (Great Britain)       Short-term value: 7 mg/m³         Long-term value: 3.5 mg/m³         7440-02-0 nickel         PEL (USA)       1 mg/m³         REL (USA)       0.015 mg/m³         Elemental       Elemental         TLV (USA)       1.5* mg/m³         Elemental;*as inhalable fraction         WEL (Great Britain)       0.5 mg/m³	INLL (USA)		
WEL (Great Britain) Short-term value: 7 mg/m³ Long-term value: 3.5 mg/m³  7440-02-0 nickel  PEL (USA) REL (USA) REL (USA) 1 mg/m³ Elemental TLV (USA) 1.5* mg/m³ Elemental;*as inhalable fraction WEL (Great Britain) 0.5 mg/m³	TIV (IISA)		
Long-term value: 3.5 mg/m³			
7440-02-0 nickel         PEL (USA)       1 mg/m³         REL (USA)       0.015 mg/m³         Elemental       1.5* mg/m³         Elemental;*as inhalable fraction         WEL (Great Britain)       0.5 mg/m³	WEE (Great Britain)		
PEL (USA) 1 mg/m³ REL (USA) 0.015 mg/m³ Elemental 1.5* mg/m³ Elemental;*as inhalable fraction WEL (Great Britain) 0.5 mg/m³	7440-02-0 nickel	g	
REL (USA)  0.015 mg/m³ Elemental  TLV (USA)  1.5* mg/m³ Elemental;*as inhalable fraction  WEL (Great Britain)  0.5 mg/m³		1 mg/m <sup>3</sup>	
Elemental 1.5* mg/m³ Elemental;*as inhalable fraction WEL (Great Britain) 0.5 mg/m³			
TLV (USA)  1.5* mg/m³  Elemental;*as inhalable fraction  WEL (Great Britain)  0.5 mg/m³	(/		
WEL (Great Britain)  Elemental;*as inhalable fraction 0.5 mg/m³	TLV (USA)		
WEL (Great Britain) 0.5 mg/m <sup>3</sup>	` ′		
	WEL (Great Britain)		
GO 141		as Ni	



## Material Safety Data Sheet

#### Additional information:

The lists that were valid during the creation were used as basis.

#### Personal protective equipment:

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with skin and eyes.

#### Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### Protection of hands:

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye protection:

Tightly sealed goggles





## Material Safety Data Sheet

### 9. Physical/Chemical Properties:

Form: Squar Color: Silver Odor: Without

Change in condition

**General Information** 

Melting point/Melting range: Not available Boiling point/Boiling range: Not available

Flash point: Not available

Flammability (solid, gaseous): Not available

Ignition temperature: Not available

Auto igniting: Not available

Danger of explosion: Not available

Explosion limits: Lower: Not available Upper: Not available

Oxidizing properties: Not available

Vapor pressure: Not available

Density: Not available

Relative density: Not available Vapour density: Not available Evaporation rate: Not available

·Solubility in / Miscibility with Water: Not available

pH-value: Not available

Viscosity: Dynamic: Not available

### 10. Stability & Reactivity:

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Materials to be avoided:

Dangerous reactions: Not available

Dangerous products of decomposition: No dangerous decomposition products known.



## Material Safety Data Sheet

### 11. Toxicological information:

Acute toxicity:

LD/LC50 values that are relevant for classification: 1333-86-4 Carbon black, Oral, LD50, 10000 mg/kg (rat)

Primary irritant effect:

On the skin: Irritating effect possible.
On the eye: Irritating effect possible.
Sensitization: Sensitization possible.

### 12. Ecological information:

Additional ecological information:

General notes:

No ecological impacts expected under normal use conditions.

The materials contained in this product may only represent below ecological impact if the integrity of the battery is compromised; physically or electrically abused.

Water hazard class 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

### 13. Disposal considerations:

Product:

Recommendation: Hand over to hazardous waste disposers.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.



## Material Safety Data Sheet

## 14. Transport Information:

DOT regulations:



Hazard class: 9
Identification number: UN3480
Packing group: II

Proper shipping name (technical name): LITHIUM ION BATTERIES

ibel:

Land transport ADR/RID (cross-border):



ADR/RID class: 9 Miscellaneous dangerous substances and articles

Danger code (Kemler): UN-Number: 3480
Packaging group: ||

Label: 9

**Description of goods:** 3480 LITHIUM ION BATTERIES

Maritime transport IMDG:



 IMDG Class:
 9

 UN Number:
 3480

 Label:
 9

 Packaging group:
 II

 EMS Number:
 F-G,S-N

 Marine pollutant:
 No

Propper shipping name: LITHIUM ION BATTERIES

Air transport ICAO-TI and IATA-DGR:



ICAO/IATA Class: 9
UN/ID Number: 3480
Label: 9
Packaging group: II

Proper shipping name: LITHIUM ION BATTERIES

Transport/Additional information: Special provisions: 188, 230, 310, 636



# Material Safety Data Sheet

## 15. Regulatory Information:

#### Sara

Section 355 (extremely hazardous substances)		
None of the ingredients is listed.		
Section 313 (Specific toxic chemical listings):		
7429-90-5	aluminium	
7440-50-8	copper	
7440-02-0	nickel	
TSCA (Toxic Substances Control Act):		
All ingredients are listed.		

### **Proposition 65**

Chemicals known to cause cancer:	
1333-86-4	Carbon black
7440-02-0	nickel
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	

### Cancerogenity categories

EPA (Environmental Protection Agency)				
7440-50-8	Copper	D		
IARC (Intern	IARC (International Agency for Research on Cancer)			
1333-86-4	Carbon black	2B		
7440-02-0	Nickel	2B		
NTP (Nation	NTP (National Toxicology Program)			
7440-02-0	nickel	R		
TLV (Threshold Limit Value established by ACGIH)				
7429-90-5	Aluminium	A4		
1333-86-4	Carbon black	A4		
7440-02-0	Nickel	A5		
NIOSH-Ca (National Institute for Occupational Safety and Health)				
1333-86-4	Carbon black			
7440-02-0	Nickel			
OSHA-Ca (Occupational Safety & Health Administration)				
None of the ingredients is listed.				



## Material Safety Data Sheet

#### Product related hazard informations:

#### Risk phrases:

The materials contained in this product may only represent below hazard if the integrity of the battery is compromised; physically or electrically abused.

Harmful in contact with skin.

Causes burns.

Limited evidence of a carcinogenic effect.

May cause sensitisation by inhalation and skin contact.

Reacts violently with water, liberating extremely flammable gases.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

### 16. Other Information:

#### DISCLAIMER OF LIABILITY

The information in this MSDS/SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in anyway connected with the handling, storage, use or disposal of the product. This MSDS/SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS/SDS information may not be applicable.

Page 10 of 10